

# AC 7000 CAN

## MODULAR SWITCH-MODE CONVERTER FOR TELECOMMUNICATION AND INDUSTRIAL APPLICATIONS

Output current of a single power supply:

125 A (for 48 V DC)

100 A (for 60 V DC)

60 A (for 110 V DC)

30 A (for 220 V DC)



### Applications

The smart switch mode power supply AC 7000 CAN of AEG Power Solutions consists of three different types of devices. The devices with 110 VDC or 220 VDC are conceived for a variety of applications such as: supply of process control to conventional power plants and nuclear power plants, secure supply of energy in conjunction with parallel connected batteries, direct power supply to DC consumers of all kinds, constant voltage and power source, on-board power supplies in railway vehicles and ships powering the DC users. The switchable device type 48 (60) VDC is specially designed to supply power to telecommunication systems and as a battery-charging rectifier for the secure supply of DC power.

### Communication

The unit offers full functionality in stand-alone mode but can additionally be controlled and monitored via the digital CAN-BUS which is immune to interference. By using the optional controller complex PSC 100 control unit, DC systems can be built up on a low cost basis. In addition to the SMR power cabling only simple BUS wiring between the SMR's and the PSC 100 is required to complete the DC system.

### Easy Operation

The connections can be easily accessed from the front panel. The lit LCD display of 2 x 16 characters show the output voltage and output current, the device status and error messages clearly.

### Compact Design

The compact 19-inch design of AC 7000 CAN converter ensure that it can be used even when there is a little space available. The unit can be configured also in the redundant systems using the N+1 principle.

### Key Features

- » Mechanical strength and vibration resistance to KTA 3503 (110 V / 220 V)
- » Low height and low weight
- » Adjustable version 48 VDC/60 VDC
- » Capable of communication (CAN-Bus)
- » When operated with PSC 100:
  - active current sharing
  - 4 charge characteristics
  - Temperature compensated battery charging
- » Future-oriented microprocessor technology
- » Lit LCD display
- » Windows-based SNT software tool for setting the output values
- » Low inrush current
- » Short circuit proof
- » CE- compliant
- » ISO 9001 certified

# AC 7000 CAN

SPECIFICATIONS

TYPE AC 7000 CAN		48 V/60 A	110 V/60 A	220 V/30 A	
Part Number		phased out	D400 G 110/60 BWrug-CFpüx	D400 G 220/30 BWrug-CFpüx	
E-Number			3 000 001 101	3 000 000 533	3 000 000 534
INPUT					
Nominal input voltage		3 x 400 V AC ± 15 %		3 x 400 V AC ± 10 %	
Frequency		47 to 63 Hz			
Current consumption (approx. values)		3 x 12 A AC			
Inrush current		≤ Rated input current			
Required mains fuse		gL 3 x 16 A or circuit breaker C-Characteristics			
OUTPUT					
		G 48/125	G 60/100	G 110/60	G 220/30
Output Voltage		53.5 V DC ± 1 %	66.9 V DC ± 1 %	122.7 V DC ± 1 %	245.3 V DC ± 1 %
Setting Range		35 to 63.6 V DC	40 to 79.5 V DC	90 to 155 V DC	180 to 310 V DC
Output Current		125 A DC ± 2 %	100 A DC ± 2 %	60 A DC ± 2 %	30 A DC ± 2 %
Setting Range		6.3 to 125 A DC	5 to 100 A DC	3 to 60 A DC	1.5 to 30 A DC
Voltage ripple		< 100 mV pp		< 250 mV pp	< 500 mV pp
Power factor		0,93		0,92	
Efficiency (%)		91	92	91	
Dynamic response		≤5 % for sudden changes in load between 10 % - 90 % - 10 % Rated output current (Compensation time t < 1 ms)			
Short circuit response		Short-circuit proof			
Parallel operation		max. 31 units, load distribution approx. 10 % if connected to CAN-BUS			
Characteristic line		IU Characteristic to DIN 41772 / DIN 41773			
MONITORING AND INDICATION					
Mains-Side Monitoring Device OFF/ON		Under-voltage / Over-voltage: with switch-off, self acknowledging OFF ≤325 V or ≥460 V / ON ≥350 V or ≤445 V			
Output-side Monitoring Systems		DC under-voltage without switch-off, self acknowledging			
Message OFF/ON		48 V DC / 50 V DC	60 V DC / 62,5 V DC	110 V DC / 115 V DC	220 V DC / 230 V DC
		DC over-voltage with switch-off and lock (software-controlled)			
Device OFF/ON		≥ 56,5 V DC / ≤ 55 V DC	≥ 70,3 V DC / ≤ 68,3 V DC	≥ 130 V DC / ≤ 125 V DC	≥ 260 V DC / ≤ 250 V DC
		DC over-voltage (hardware-controlled)			
		70 V DC	85 V DC	160 V DC	320 V DC
Alerts and Indicators		U <sub>A</sub> and I <sub>A</sub> via LCD 2 x 16 characters, lit Loading: LED green Fault: LED red			
		Fault message via floating relay contact; Display of the error memory			
		ON/OFF via external floating contact			
MECHANICAL					
Design		19" module for installation in sub frame to DIN 41494			
Ingress Protection		IP 20			
Mechanical Strength and Vibration Resistance		to EN 50178 Section 9.4.3.2			
Equipment Colour		Colour RAL 7035 (Front panel)			
Dimensions W x H x D (mm)		483 x 221.4 x 400 (19" x 5 HE)			
Weight		approx. 30 kg			
Mains connection		Angle plug type GDME 313			
DC-Output		Threaded bolt M10			
Conductor		Thread M6			
Signals interface		CombiCon type MSTB 2.5/3-STF-5.08 3-pole			
ENVIRONMENTAL					
Type of cooling		Forced air cooling			
Operating Temperature Range		0 °C to 40 °C, when installed in cabinet			
Storage temperature range		-30 °C to 70 °C			
Environment Conditions		EN 60721 part 3 - 3, Class 3K3 / 3Z1 / 3B1 / 3C2 / 3S2 / 3M2			
Installation height		max 1,000 m above sea level, at nominal load			
STANDARDS					
Interference emission		to EN 61000-6-4			
Interference resistance		to EN 61000-6-2			
Low voltage function with safe disconnection		to EN 50178			
Approvals		CE			
Certificate		ISO 9001			

AC7000 -EN-12-2013-V1 - Due to our policy of continuous development, data in this document is subject to change without notice and becomes contractual only after written confirmation. AEG is a registered trademark used under license from AB Electrolux.

## AEG Power Solutions GmbH

Emil-Siepmann-Str. 32  
D-59581 Warstein-Belecke  
Germany

Phone: +49 2902 763 143  
Fax: +49 2902 763 1203

smr@aegps.com  
www.aegps.com

**AEG**  
POWER SOLUTIONS